JAMES M. BRUGGER et al. Application No.: 09/595,167

Page 10

CLEAN VERSION OF ALL PENDING CLAIMS

IN THE CLAIMS:

1. (Amended) An implantable port comprising:

a port body having a flow passage therethrough, said flow passage having an upstream end and a downstream end, wherein at least a portion of the upstream end is adapted to sealingly engage an access tube which is inserted into said upstream end; and

a pressure-responsive valve element positioned in the flow passage within the port body downstream from the upstream portion so that an access tube can be fully inserted into said upstream portion without engaging the valve component, wherein the valve component is closed in the absence of a differential pressure above a threshold level.

- 2. (Amended) An implantable port as in claim 1, wherein said port body comprises a housing and a housing insert coupled to said housing.
- 3. (As filed) An implantable port as in claim 2 wherein said insert comprises a compliant material defining a portion of the flow passage.
- 4. (Withdrawn) An implantable port as in claim 2 wherein said insert comprises a nipple element containing said pressure-responsive valve.
- 5. (As filed) An implantable port as in claim 2 wherein said portion of the upstream end of the housing adapted to sealingly engage the access tube has a radial stiffness greater than a radial stiffness of said access tube.
- 6. (As filed) An implantable port as in claim 2 wherein said housing comprises stainless steel.

JAMES M. BRUGGER et al. Application No.: 09/595,167

Page 11

- 7. (As filed) An implantable port as in claim 2 wherein the housing defines a first portion of the passage and the insert defines a second portion of the passage.
- 8. (Withdrawn) An implantable port as in claim 7 wherein the first portion of the passage has a distal opening with a diameter smaller than a diameter of the access tube.

Please cancel claim 9.

- 10. (As filed) An implantable port as in claim 1, wherein the downstream end of the flow passage is disclosed at about a 90° angle relative to the upstream end which receives the access tube.
- 11. (Withdrawn) An implantable port as in claim 1 wherein the passage does not have a needle guide channel coupled to the body and upstream of the upstream end of the passage.
- 12. (As filed) An implantable port as in claim 1, wherein said valve element comprises a pressure-responsive slit valve.
- 13. (Withdrawn) An implantable port as in claim 1, wherein said valve element comprises an articulating, pressure-responsive leaflet valve.
- 14. (Amended) An implantable port as in claim 1 wherein the flow passage further comprises a catheter coupled to said port body wherein said catheter has a lumen fluidly coupled to said passage in the port body.

Please cancel claim 15.

16. (As filed) An implantable port as in claim 1, wherein the threshold valve of the differential pressure is between about 0.25 and 25.0 psi.

JAMES M. BRUGGER et al. Application No.: 09/595,167

Page 12

17. (Amended) A method for delivering a substance to a subcutaneous target site, said method comprising:

percutaneously introducing an access tube to an implanted port having a flow passageway with an upstream end, a downstream end, and a valve element in the flow passageway within the port, wherein the access tube is introduced to seat in the passage but does not engage the valve element; and

introducing said substance into the flow passage through the access tube at a pressure sufficient to open the valve element to permit flow through the flow passageway to the target site.

- 18. (As filed) A method as in claim 17 further comprising repeatedly accessing the implanted port with said access tube through the same access tract at intervals and over a time period sufficient to cause scar tissue formation over the access tract.
- 19. (As filed) A method as in claim 17 further comprising locating said implanted port by manually aligning the access tube with a line from the skin entry point of an access tract to the aperture on the port.
- 20. (Amended) A method as in claim 17 further comprising locating the port by manually feeling the port to determine the position of the aperture.
- 21. (Amended) A method as in claim 17, wherein percutaneously introducing further comprises introducing the access tube through a skin layer overlying the implanted port having a thickness in the range from 3 mm to 20 mm.
- 22. (As filed) A method as in claim 17, wherein the access tube comprises a blunt cannula.
- 23. (As filed) A method as in claim 17, wherein the introducing step comprises orienting the access tube generally vertically with respect to the skin surface.

JAMES M. BRUGGER et al. Application No.: 09/595,167 Page 13

24. (As filed) A kit comprising:

a subcutaneously implantable port according to claim 1;

instructions for implanting the port comprising implanting a port in a subcutaneous tissue pocket, wherein an access cannula-receiving aperture of the port is disposed beneath an intact region of skin, and introducing a penetrating element through the intact region of skin into the aperture, wherein the element remains anchored in the aperture for a time sufficient to create an access tract; and

a package adapted to contain the port and the instructions for use.

- 25. (Amended) A kit as in claim 24, further comprising a penetrating element.
- 26. (Amended) A kit as in claim 25, wherein the penetrating element comprises a syringe needle.
- 27. (New) An implantable port as in claim 2, wherein the pressureresponsive valve element is integrally formed in the housing insert.

PA 3237767 v1